

Guide Wires

Single Use & Autoclavable

Bavarian Guide Wires

- Teflon Coated Nitinol Wire
Kink Resistant
Usable During Sphincterotomy
- Hydrophilically Coated
Easy, Low Friction Advancement
- Radiopaque Tip
Enhanced Visibility
- Autoclavable
Reusable If Device Integrity Is Intact

Cyst Guide Wire

- Uncoated Nitinol Wire
Kink Resistant
Compatible with 19 Gauge EUS-FNA Systems for Cyst Drainage

Guide Wires

Single Use & Autoclavable

Guide Wires

Bavarian Guide Wires are mainly indicated for cannulation and placement of diagnostic and therapeutic instruments in the biliary and pancreatic systems. The guide wire may be left in place during sphincterotomy. Users can choose between a "Soft Tip" and a slightly stiffer "Standard Tip" version. A shorter length guide wire is offered for use in combination with the available short wire systems. The guide wire is autoclavable and accepts a reuse, depending of the instrument integrity after the firsttime use.

Cyst Guide Wire is exclusively indicated for introduction and advancement through a 19-Gauge EUS-FNA system and perfect for the placement of plastic stents, (primarily double pigtail stents) in cyst drainage applications. The uncoated guide wire allows smooth and precise performance through a beveled EUS-FNA needle.

Standard Guide Wires are cost effective alternatives for a wide range of endoscopic procedures that require use of a guide wire. NOTE: This type of guide wire is not applicable for sphincterotomy.

Bavarian Wires

Hydrophilically Teflon coated Nitinol Wire, bi-color with a 5 cm tapered radiopaque tip, autoclavable, sterile packed

Catalog No.	Description	Diameter	Length
GGW-03-21-400	"Soft" Tip	.021" (0.53 mm)	400 cm
GGW-03-21-450	"Soft" Tip	.021" (0.53 mm)	450 cm
GGW-03-25-450	"Soft" Tip	.025" (0.64 mm)	450 cm
GGW-03-35-400	"Soft" Tip	.035" (0.89 mm)	400 cm
GGW-03-35-450	"Soft" Tip	.035" (0.89 mm)	450 cm
GGW-04-35-400	"Standard" Tip	.035" (0.89 mm)	400 cm
GGW-04-35-450	"Standard" Tip	.035" (0.89 mm)	450 cm

Bavarian Wires – For Short Wire Systems

Hydrophilically Teflon coated Nitinol Wire, bi-color with a 5 cm tapered radiopaque tip, autoclavable, sterile packed

Catalog No.	Description	Diameter	Length
GGW-03-21-260	"Soft" Tip	.021" (0.53 mm)	260 cm
GGW-03-25-260	"Soft" Tip	.025" (0.64 mm)	260 cm
GGW-03-35-260	"Soft" Tip	.035" (0.89 mm)	260 cm

Cyst Guide Wire – Compatible with 19-Gauge EUS-FNA Systems for Cyst Drainage

Uncoated Nitinol Wire, single use, sterile packed

Catalog No.	Description	Diameter	Length
GGW-08-30-400	15 cm flexible radiopaque tip	.030" (0,75 mm)	400 cm

Standard Guide Wires – Teflon coated Stainless Steel Wire, single use, sterile packed

Catalog No.	Description	Diameter	Length
GGW-01-35-400	Fixed Core	.035" (0.89 mm)	400 cm
GGW-01-35-450	Fixed Core	.035" (0.89 mm)	450 cm
GGW-02-35-400	Movable Core	.035" (0.89 mm)	400 cm
GGW-02-35-450	MovableCore	.035" (0.89 mm)	450 cm